

THE BEST CHOICE FOR BAKERIES PRODUCING A WIDE VARIETY OF PRODUCTS WITH A LOW VOLUME PRODUCTION.

EZ DIVIDER

CX011

Suitable for any type of dough!

Ideal for all types of dough: additive-free, natural yeast, long fermentation, high water absorption, rice flour, and more.

Accepts all types of dough-making methods!


Good for straight dough, sponge dough, overnight dough, brew dough, and all other methods.



Divides dough quickly and accurately like a professional.









Place the dough on the conveyor from a tray. Then all you have to do is enter the cutting and weight and push the start button.

- Set the product weight and number of products and the machine will do the rest. Divides even as light as 20g of dough.
- The STRESS FREE system causes no damage to the dough and makes high quality products.
- Processes all types of dough: long fermentation, natural yeast, lean, high water absorption, and more.
- Solid ingredients such as raisins and nuts keep their shapes intact. Experience the smooth product changeover since the interior of the machine remains clean.
- Divides the dough without any residues.

Divides into preset

number of dough pieces.

Dough Flow Direction

Just plug in the power, you're ready to go. Quiet operation due to the servo driven guillotine cutter.

Two distinctive production modes offer high efficient portioning.

Weighing cut mode

Weight accuracy in dividing the dough. Forms a batch of dough placed on the conveyor into a continuous strip of dough, weighs and divides the dough with high accuracy using the "Gravimetric method"



and divides




Provides corrected feed back **Gravimetric** method



20 g: about 2400 pcs/hour 350 g: about 450 pcs/hour

Weighs and divides into consistent weight.



require consistent size.






Traditional baguettes can

Baguette mode

Divides the dough on the conveyor evenly. Cuts the divided dough into equal sized pieces if needed. Useful for making products such as baguettes and rustiques that

Divides the width evenly.



be baked right after dough dividing!

Easy operation

Retrieve the product data from the memory and simply start production. Up to 100 production data can be memorized.




Easy cleaning and storage

Parts can be removed easily and safely. Conveyor folds compactly



space-saving storage after production.

Dimensions



Specifications

· · · · · · · · · · · · · · · · · · ·	
Length	2081 mm
Width	1240 mm
wiain	1240 11111
Height	1384 mm
Weight	300 kg
Electrical Capacity	0.59 kW
Production Capacity	*40 shots/min
Product Weight Range	20 - 350 g
Maximum dough weight on conveyor	7 - 8 kg

Actual weight range and maximum production capacity can vary depending on dough condition and supplied amount. Please test your products to find your actual numbers.

The specifications are subject to change without notice and without obligation. All Rights Reserved. Reproduction, adaptation or translation without prior written permission is prohibited.

RHEON AUTOMATIC MACHINERY CO., LTD.
Head Office: 2-3 Nozawa-machi, Utsunomiya 320-0071, Japan
Phone: 028-665-1111 Fax: 028-665-3346 E-mail: info@rheon.com

2 Doppler, Irvine, CA 92618, U.S.A.
Phone: 949-768-1900 Fax: 949-855-1991 E-mail: us.info@rheon.com
URL:http://www.rheonusa.com

RHEON U.S.A. NJ BRANCH

URL:https://www.rheon-europe.com

700 Huyler Street Teterboro, NJ 07608, U.S.A. Phone: 201-487-0600 Fax: 201-487-0610 E-mail: us.east@rheon.com

RHEON AUTOMATIC MACHINERY GmbH Tiefenbroicher Weg 30, 40472 Düsseldorf, Germany Phone: 0211-471950 Fax: 0211-424129 E-mail: de.info@rheon.com

RHEON AUTOMATIC MACHINERY GmbH ULM BRANCH
Saumweg 30, 89257 Illertissen, Germany
Phone: 07303-1599410 Fax: 07303-15994111 E-mail: de.info@rheon.com
RHEON AUTOMATIC MACHINERY CO., LTD. TAIWAN BRANCH
5F., No.118, Xinhu 1st Rd., Neihu District, Taipei City, Taiwan (R.O.C.)
Phone: 02-2792-3525 Fax: 02-2792-3529 E-mail: tw.info@rheon.com
RHEON AUTOMATIC MACHINERY CO., LTD. SHANGHAI OFFICE ROOM30, 5F GIFCII, 1438Hongqiao Road, changning District, Shanghai Phone: 86-21-61976378 Fax: 86-21-61976380